

路基设计表

桩号	平曲线		纵坡 (%) 及坡长 (米)	竖曲线		设计高		填挖高度 (米)		路基宽 (米)		路边及中桩与 设计高之差(米)				施工时中桩 (米)		边坡 1:1		护坡道				边沟				坡脚坡口 至 中桩距离		备注							
																				护坡道宽(米)		边坡:m		坡度(%)		形状	底宽				沟深	内坡					
	左	右		凸	凹	未计 竖曲线 设计高	改正值 + - 改正后 设计高	填	挖	左	右	左	中桩	右	填	挖	左	右	左	右	左	右	左	右													
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34				
K0+0.000	L=435.31 α=287.362°					12.257			12.257	0.64	5.75	5.75	-0.122	0	-0.123		0.64	1	1						-1.709	-1.709	矩形	0.5	0.5	∞	8.498	8.259					
K0+20.000						11.915			11.915	1.162	5.75	5.75	-0.123	0	-0.123		1.162	1	1									-1.709	-1.709	矩形	0.5	0.5		∞	9.216	8.844	
K0+40.000						11.573			11.573	1.753	5.75	5.75	-0.122	0	-0.123		1.753	1	1									-1.709	-1.709	矩形	0.5	0.5		∞	9.974	9.07	
K0+60.000						11.232			11.232	2.67	5.75	5.75	-0.123	0	-0.123		2.67	1	1										-1.709	-1.709	矩形	0.5		0.5	∞	10.949	9.902
K0+80.000						10.89			10.89	2.479	5.75	5.75	-0.123	0	-0.123		2.479	1	1										-1.709	-1.709	矩形	0.5		0.5	∞	10.417	10.224
K0+100.000	L=435.31 α=287.362°					10.548			10.548	2.196	5.75	5.75	-0.122	0	-0.122		2.196	1	1							-1.709	-1.709	矩形	0.5	0.5	∞	10.029	10.003				
K0+120.000						10.206			10.206	1.933	5.75	5.75	-0.122	0	-0.122		1.933	1	1										-1.709	-1.709	矩形	0.5	0.5		∞	9.494	9.853
K0+140.000						9.864			9.864	1.082	5.75	5.75	-0.123	0	-0.122		1.082	1	1										-1.709	-1.709	矩形	0.5	0.5		∞	8.707	8.96
K0+160.000						9.522			9.522	0.505	5.75	5.75	-0.123	0	-0.122		0.505	-1	1										-5.152	-1.709	矩形	0.5	0.5		∞	9.522	8.365
K0+180.000						K0+188.345		9.038	9.181	0.101		9.282		0.055	5.75	5.75	-0.123	0	-0.122		0.055	1	1							0.529	-3.014	梯形	0.5		0.5	1	10.171
K0+200.000	L=435.31 α=287.362°					9.194	0.069		9.264	0.151	5.75	5.75	-0.122	0	-0.123		0.151	1	-1							2.154	3.609	梯形	0.5	0.5	1	9.708	9.816				
K0+220.000						9.463			9.463	0.393	5.75	5.75	-0.122	0	-0.123		0.393	1	1										1.341	-1.516	梯形	0.5	0.5		1	8.444	9.354
K0+240.000						9.731			9.731	0.592	5.75	5.75	-0.123	0	-0.123		0.592	1	-1										1.341	2.768	梯形	0.5	0.5		1	8.643	9.695
K0+260.000						9.999			9.999	0.196	5.75	5.75	-0.123	0	-0.123		0.196	-1	-1										-2.676	0.076	梯形	0.5	0.5		1	9.775	9.981
K0+280.000						10.267			10.267	0.33	5.75	5.75	-0.122	0	-0.123		0.33																		5.75	5.75	
K0+300.000	10.536			10.536	0.415	5.75	5.75	-0.122	0	-0.123		0.415																	5.75	5.75							
K0+320.000	10.804			10.804	0.031	5.75	5.75	-0.123	0	-0.123		0.031	-1	-1											-4.075	-2.397	梯形	0.5	0.5	1	10.225	10.022					
K0+340.000	11.072			11.072	1.005	5.75	5.75	-0.122	0	-0.123		1.005	1	1											-0.273	-3.778	梯形	0.5	0.5	1	11.682	11.406					
K0+360.000	11.34			11.341	1.164	5.75	5.75	-0.122	0	-0.123		1.164	1	1											2.15	-0.243	梯形	0.5	0.5	1	11.542	11.949					
K0+380.000	11.609			11.609	0.916	5.75	5.75	-0.122	0	-0.123		0.916	1	-1											1.7	2.42	梯形	0.5	0.5	1	11.187	11.943					
K0+400.000	L=435.31 α=287.362°					11.877		0.002	11.875	1.075	5.75	5.75	-0.123	0	-0.123		1.075		1	-1						-1.152	-2.699	梯形	0.5	0.5	1	11.588	12.327				
K0+420.000						12.145		0.107	12.039	1.533	5.75	5.75	-0.122	0	-0.123		1.533		1	-1									0.037	1.528	梯形	0.5	0.5		1	12.027	13.371
K0+440.000						12.063		0.022	12.042	1.635	5.75	5.75	-0.123	0	-0.123		1.635		-1	-1										-3.242	-0.496	梯形	0.5		0.5	1	12.099