

路基设计表

桩号	平曲线		纵坡 (%) 及坡长 (米)	竖曲线		设计高			填挖高度 (米)		路基宽 (米)		路边及中桩与 设计高之差(米)			施工时中桩 (米)		边坡 1:1		护坡道			边沟				坡脚坡口 至 中桩距离		备注				
	左	右		凸	凹	未计 竖曲线 设计高	改正值		改正后 设计高	填	挖	左	右	左	中桩	右	填	挖	左	右	左	右	左	右	左	右	左	右					
							+	-																									
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
K0+460.000	A=219.089 Ls=80					11.903			11.904	1.851		5.75	5.75	-0.123	0	-0.123	1.851		-1	-1					-3.22	-0.904	梯形	0.5	0.5	1	12.854	13.079	
K0+480.000						11.743			11.744	1.981		5.75	5.75	-0.123	0	-0.123	1.981		1	1					0.031	-0.172	梯形	0.5	0.5	1	12.889	13.041	
K0+500.000						11.584			11.584	0.912		5.75	5.75	0	0	-0.122	0.912		1	1					8.868	2.387	梯形	0.5	0.5	1	11.252	12.525	
K0+520.000						11.424			11.424		0.682	5.75	5.75	0.127	0	-0.172		0.682	-1	-1					-1.663	3.9	梯形	0.5	0.5	1	9.551	9.765	
K0+540.000	R=600 E=17.93 T=185.954 Ly=206.154					11.264			11.264		0.602	5.75	5.75	0.127	0	-0.172		0.602	-1	1					-3.229	-0.8	矩形	0.5	0.5	∞	9.793	8.56	
K0+560.000						11.104			11.104		0.17	5.75	5.75	0.127	0	-0.172		0.17	-1	1					-1.966	-2.889	梯形	0.5	0.5	1	10.223	9.555	
K0+580.000						10.944			10.944		0.167	5.75	5.75	0.127	0	-0.172		0.167	1	1					-0.13	0.156	梯形	0.5	0.5	1	10.131	9.689	
K0+600.000						10.784			10.784		0.064	5.75	5.75	0.127	0	-0.172		0.064	-1	1					-5.21	-4.764	梯形	0.5	0.5	1	10.728	9.701	
K0+620.000	JD1 αy=27.326°					10.624			10.624	0.761		5.75	5.75	0.127	0	-0.172	0.761		1	1					0.772	-4.64	梯形	0.5	0.5	1	11.676	10.88	
K0+640.000						10.464			10.465	0.568		5.75	5.75	0.127	0	-0.172	0.568		-1	-1					0.461	-1.485	梯形	0.5	0.5	1	11.227	11.362	
K0+660.000						10.304			10.305	0.457		5.75	5.75	0.127	0	-0.172	0.457		-1	-1					-0.86	1.125	梯形	0.5	0.5	1	11.106	11.466	
K0+680.000						10.145			10.145	0.416		5.75	5.75	0.127	0	-0.172	0.416		1	-1					0.108	0.994	梯形	0.5	0.5	1	11.018	10.885	
K0+700.000	A=219.089 Ls=80					9.985			9.985	0.345		5.75	5.75	0.127	0	-0.172	0.345		1	-1					0.105	-1.335	梯形	0.5	0.5	1	10.835	10.74	
K0+720.000						9.825			9.825	0.015		5.75	5.75	0.127	0	-0.172	0.015		-1.5	-1					1.84	3.301	梯形	0.5	0.5	1	10.017	10.78	
K0+740.000						9.665			9.665		0.726	5.75	5.75	-0.027	0	-0.123		0.726	1	-1					-1.633	1.784	梯形	0.5	0.5	1	8.438	9.858	
K0+760.000						9.505			9.505		0.889	5.75	5.75	-0.123	0	-0.122		0.889	1	-1					-0.799	-0.8	矩形	0.5	0.5	∞	8.887	8.32	
K0+780.000	L=298.82 α=314.688°					9.345			9.345		0.884	5.75	5.75	-0.123	0	-0.122		0.884	1	1					-0.799	-0.8	矩形	0.5	0.5	∞	8.714	8.445	
K0+800.000						9.185			9.185		0.881	5.75	5.75	-0.123	0	-0.122		0.881	1	1					-0.8	-0.799	矩形	0.5	0.5	∞	8.547	8.661	
K0+820.000						9.025			9.025		1.063	5.75	5.75	-0.123	0	-0.122		1.063	1	1					-0.8	-0.8	矩形	0.5	0.5	∞	8.783	8.804	
K0+840.000						8.865			8.865		1.445	5.75	5.75	-0.123	0	-0.122		1.445	1	1					-0.8	-0.8	矩形	0.5	0.5	∞	9.047	9.288	
K0+860.000	JD1 αy=27.326°					8.706			8.706		2.084	5.75	5.75	-0.123	0	-0.122		2.084	1	1					-0.8	-0.8	矩形	0.5	0.5	∞	9.608	9.848	
K0+880.000						8.546			8.546		2.374	5.75	5.75	-0.123	0	-0.122		2.374	1	1					-0.8	-0.8	矩形	0.5	0.5	∞	9.862	9.863	
K0+900.000						8.386			8.386		1.885	5.75	5.75	-0.123	0	-0.122		1.885	1	1					-0.8	-0.8	矩形	0.5	0.5	∞	9.426	9.536	