

路基设计表

桩号	平曲线		纵坡 (%) 及坡长 (米)	竖曲线		设计高			填挖高度 (米)		路基宽 (米)		路边及中桩与 设计高之差(米)			施工时中桩 (米)		边坡 1:1		护坡道					边沟					坡脚坡口 至 中桩距离			备注
	左	右		凸	凹	未计 竖曲线 设计高	改正值 +	-	改正后 的设计高	填	挖	左	右	左	中桩	右	填	挖	左	右	左	右	左	右	左	右	左	右	左	右			
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
K0+920.000	L=298.82 α=314.688°					8.226			8.226		1.317	5.75	5.75	-0.123	0	-0.122		1.317	1	1					-0.8	-0.8	矩形	0.5	0.5	∞	8.756	9.367	
K0+940.000						8.066			8.066		0.854	5.75	5.75	-0.123	0	-0.122		0.854	1	1					-0.8	-0.8	矩形	0.5	0.5	∞	8.424	8.919	
K0+960.000						7.906	0.016		7.922		0.886	5.75	5.75	-0.123	0	-0.123		0.886	1	1					-0.527	-0.527	矩形	0.5	0.5	∞	8.521	8.467	
K0+980.000						K0+978.279	7.76				0.497	5.75	5.75	-0.123	0	-0.122		0.497	1	-1					0.383	-3.007	梯形	0.5	0.5	1	8.555	9.788	
K1+0.000	A=219.089 Ls=80					7.784	0.131		7.914		0.7	5.75	5.75	-0.123	0	-0.123		0.7	1	1	-1				1.111	4.142	梯形	0.5	0.5	1	8.496	9.623	
K1+20.000						8.337			8.337		1.037	5.75	5.75	-0.122	0	-0.122		1.037	1	1					1.384	1.384	矩形	0.5	0.5	∞	8.936	8.5	
K1+40.000						8.614			8.614		1.33	5.75	5.75	-0.122	0	-0.122		1.33	1	1					1.384	1.384	矩形	0.5	0.5	∞	9.244	8.839	
K1+60.000						8.891			8.891		1.553	5.75	5.75	-0.122	0	-0.122		1.553	1	1					1.384	1.384	矩形	0.5	0.5	∞	9.584	9.339	
K1+80.000	JD2 αz=24.702° R=600 E=14.671 T=171.472 Ly=178.678					9.167			9.167		1.761	5.75	5.75	-0.122	0	-0.122		1.761	1	1	1				1.384	1.384	矩形	0.5	0.5	∞	9.937	9.32	
K1+100.000						9.444			9.444		2.153	5.75	5.75	-0.122	0	-0.122		2.153	1	1					1.384	1.384	矩形	0.5	0.5	∞	10.377	9.418	
K1+120.000						9.721			9.721		2.916	5.75	5.75	-0.122	0	-0.122		2.916	1	1					1.383	1.384	矩形	0.5	0.5	∞	11.358	9.751	
K1+140.000						9.997			9.997		4.072	5.75	5.75	-0.122	0	-0.122		4.072	1	1					1.383	1.384	矩形	0.5	0.5	∞	11.444	10.684	
K1+160.000	A=219.089 Ls=80					10.274			10.274		3.38	5.75	5.75	-0.122	0	-0.042		3.38	1	1	1				1.383	2.217	矩形	0.5	0.5	∞	10.171	10.927	
K1+180.000						10.551			10.551		2.257	5.75	5.75	-0.17	0	0.125		2.257	1	1					0.547	2.218	矩形	0.5	0.5	∞	9.547	9.936	
K1+200.000						10.828			10.828		1.884	5.75	5.75	-0.173	0	0.128		1.884	1	1					1.384	1.383	矩形	0.5	0.5	∞	9.208	9.712	
K1+220.000						11.104			11.104		1.75	5.75	5.75	-0.173	0	0.128		1.75	1	1					1.383	1.384	矩形	0.5	0.5	∞	9.255	9.506	
K1+240.000	JD2 αz=24.702° R=600 E=14.671 T=171.472 Ly=178.678					11.381			11.381		1.547	5.75	5.75	-0.173	0	0.128		1.547	1	1	1				1.382	1.383	矩形	0.5	0.5	∞	9.036	9.017	
K1+260.000																																	
K1+280.000						K1+271.298	11.814																										
K1+300.000						R=7000	E=0.051	T=26.643																									
K1+320.000	A=219.089 Ls=80					12.117			12.117		0.98	5.75	5.75	-0.173	0	0.127		0.98	1	1	1				0.622	0.623	矩形	0.5	0.5	∞	8.46	8.888	
K1+340.000						12.242			12.241		2.204	5.75	5.75	-0.173	0	0.127		2.204	1	1					0.622	0.622	矩形	0.5	0.5	∞	10.022	9.7	
K1+360.000						12.366			12.366		2.147	5.75	5.75	-0.164	0	0.119		2.147	1	1					1.457	-0.211	矩形	0.5	0.5	∞	9.733	9.37	