

路基设计表

桩号	平曲线		纵坡 (%) 及坡长 (米)	竖曲线		设计高			填挖高度 (米)		路基宽 (米)		路边及中桩与 设计高之差(米)			施工时中桩 (米)		边坡 1:1		护坡道			边沟					坡脚坡口 至 中桩距离		备注			
	左	右		凸	凹	未计 竖曲线 设计高	改正值 +	-	改正后 设计高	填	挖	左	右	左	中桩	右	填	挖	左	右	左	右	左	右	左	右	左	右					
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
K1+380.000	平曲线 L=451.988 a=289.986°		0.622 238.79	K1+510.088 13.3	R=3000 E=0.142 T=29.149	12.49			12.49		0.695	5.75	5.75	-0.122	0	-0.048		0.695	1	-1					0.622	-0.211	矩形	0.5	0.5	∞	8.492	8.281	
K1+400.000						12.615			12.615	1.257		5.75	5.75	-0.123	0	-0.122	1.257		1	1					-0.996	-9.8	梯形	0.5	0.5	1	11.597	12.113	
K1+420.000						12.739			12.739	1.598		5.75	5.75	-0.123	0	-0.122	1.598		1	1					-1.258	1.273	梯形	0.5	0.5	1	12.115	12.778	
K1+440.000						12.864			12.864	0.66		5.75	5.75	-0.123	0	-0.122	0.66		1	-1					6.501	8.805	梯形	0.5	0.5	1	10.583	11.378	
K1+460.000						12.988			12.988			5.75	5.75	-0.123	0	-0.122		0.516	1	-1					0.622	3.17	梯形	0.5	0.5	1	8.67	9.534	
K1+480.000	纵坡 0.622 238.79		K1+510.088 13.3	R=3000 E=0.142 T=29.149	13.113			13.112		1.249	5.75	5.75	-0.123	0	-0.122		1.249	1	1						0.622	0.622	矩形	0.5	0.5	∞	9.254	8.771	
K1+500.000					13.237		0.061	13.176		1.069	5.75	5.75	-0.123	0	-0.122		1.069	1	1					0.055	0.055	矩形	0.5	0.5	∞	9.082	8.511		
K1+520.000					13.169		0.062	13.107	0.561	5.75	5.75	-0.123	0	-0.122		0.561	-1	-1					-0.754	-3.413	梯形	0.5	0.5	1	8.284	9.6			
K1+540.000					12.905			12.905	0.894		5.75	5.75	-0.122	0	-0.122	0.894		-1	1					-11.226	-9.722	梯形	0.5	0.5	1	12.172	10.918		
K1+560.000					12.641			12.64	1.534		5.75	5.75	-0.123	0	-0.123	1.534		-1	1					1.471	3.531	梯形	0.5	0.5	1	12.88	12.324		
K1+580.000	纵坡 13.3		K1+510.088 13.3	R=3000 E=0.142 T=29.149	12.376			12.376	0.889		5.75	5.75	-0.123	0	-0.123	0.889			-1	1					4.645	4.238	梯形	0.5	0.5	1	11.709	11.203	
K1+600.000					12.112			12.112		0.291	5.75	5.75	-0.122	0	-0.122		0.291	-1	-1					5.281	4.238	梯形	0.5	0.5	1	9.779	9.428		
K1+620.000					11.848			11.848		1.148	5.75	5.75	-0.122	0	-0.122		1.148	1	1					-1.321	-1.321	矩形	0.5	0.5	∞	8.689	8.739		
K1+640.000					11.584			11.584		1.541	5.75	5.75	-0.123	0	-0.123		1.541	1	1					-1.321	-1.321	矩形	0.5	0.5	∞	9.249	9.205		
K1+660.000					11.32			11.32		1.525	5.75	5.75	-0.123	0	-0.123		1.525	1	1					-1.321	-1.321	矩形	0.5	0.5	∞	9.157	9.355		
K1+680.000	纵坡 L=451.988 a=289.986°		纵坡 (%) 及坡长 (米)	K1+510.088 13.3	R=3000 E=0.142 T=29.149	11.056			11.055		0.933	5.75	5.75	-0.122	0	-0.122		0.933	1	1					-1.321	-1.321	矩形	0.5	0.5	∞	8.446	8.826	
K1+700.000						10.791			10.791	0.398		5.75	5.75	-0.123	0	-0.123	0.398		1	1					-4.999	-6.525	梯形	0.5	0.5	1	10.595	10.419	
K1+720.000						10.527			10.527	0.451		5.75	5.75	-0.123	0	-0.123	0.451		1	1					-1.328	0.001	梯形	0.5	0.5	1	10.708	10.674	
K1+740.000						10.263			10.263	0.269		5.75	5.75	-0.122	0	-0.122	0.269		-1	1					-1.065	-0.693	梯形	0.5	0.5	1	10.61	10.371	
K1+760.000						9.999			9.999	0.199		5.75	5.75	-0.122	0	-0.122	0.199		1	1					-0.681	-0.703	梯形	0.5	0.5	1	10.473	10.251	
K1+780.000	纵坡 0.622 238.79		K1+510.088 13.3	R=3000 E=0.142 T=29.149	9.735			9.735		0.062	5.75	5.75	-0.123	0	-0.123		0.062	1	1					-3.583	-0.703	梯形	0.5	0.5	1	9.922	10.119		
K1+800.000					9.47			9.47	0.369		5.75	5.75	-0.123	0	-0.123	0.369		1	1					-1.152	-2.466	梯形	0.5	0.5	1	10.641	10.394		
K1+820.000					9.206			9.206	0.722		5.75	5.75	-0.122	0	-0.122	0.722		1	1					-5.168	-3.194	梯形	0.5	0.5	1	11.568	10.885		